

Appl. No. 10/025,628

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Original) A method in a computer system for displaying network management information for an optical network, said optical network comprising a plurality of nodes each comprising at least one optical component, and a plurality of links for transmitting optical signals between said plurality of nodes, said optical network further comprising at least one route of optical signal transmission, said route comprising a start node, an end node, and intermediate nodes and intermediate links through which an optical signal is transmitted between the start node and the end node on the route, wherein the intermediate links of said route are composed of a plurality of channels, and each of said channels is composed of at least one longitudinal segment, each of which longitudinal segments may be provisioned for data traffic by a network administrator, and wherein each of said optical signals is a multiplexed combination of a plurality of channel signals, each of said channel signals having associated therewith, a transmitter optical component and a receiver optical component, the method comprising:

upon selection of a network topology icon:

identifying in the plurality of nodes, add/drop nodes at which a channel signal may be added to, and/or dropped from, an optical signal on the optical network;

displaying a network topology panel; and

displaying in the network topology panel, a graphical representation of only those of the plurality of nodes which have been identified as add/drop nodes;

upon selection of an optical components icon:

awaiting selection of a selected route;

upon selection of a selected route, identifying the start node, at least one intermediate node, and the end node, of which the selected route is comprised;

Appl. No. 10/025,628

displaying an optical components panel; and

displaying in the optical components panel graphical representations of at least one optical component of which the start node is comprised, at least one optical component of which the at least one intermediate node is comprised, and at least one optical component of which the end node is comprised, as identified for the selected route;

upon selection of a channel viewer icon:

awaiting selection of a selected route;

upon selection of a selected route, identifying each of the plurality of channels of which the links of the selected route are comprised;

displaying a channel viewer panel;

displaying in the channel viewer panel, a graphical representation of each of the plurality of channels identified for the selected route; and

communicating in association with each of the graphical representations of the channels, which of the longitudinal segments of which the channel is comprised, has been provisioned for data traffic by the network administrator; and

upon selection of a transmitters/receivers icon:

awaiting selection of a selected route;

upon selection of a selected route, identifying information respecting the transmitter optical component and receiver optical component associated with the channel signal transmitted by each of the channels of which the links of the selected route are composed;

displaying a transmitters/receivers panel; and

Appl. No. 10/025,628

displaying in tabular form in the transmitters/receivers panel, the information respecting each of the transmitter optical components and the receiver optical components identified for the selected route.

2. (Original) The method of claim 1 further comprising:

when the network topology icon has been selected, displaying in the network topology panel, a graphical representation of those of the plurality of links which transmit optical signals between the add/drop nodes.

3. (Original) The method of claim 2 further comprising:

when the network topology icon and a selected route have been selected, visually distinguishing in the network topology, the graphical representations of the start node, the end node, those of the intermediate nodes at which a channel signal may be added to and/or dropped from an optical signal being transmitted on the selected route, and the intermediate links, of which the selected route is comprised.

4. (Original) The method of claim 1 wherein when the optical components icon has been selected, the graphical representations of the optical components are displayed in a linear configuration, in a sequential order.

5. (Original) The method of claim 1 further comprising:

when the optical components icon has been selected, visually communicating in the optical components panel, a proportion of a traffic capacity of each link of which the selected route is comprised, which has been provisioned for data traffic by a network administrator.

6. (Original) The method of claim 5 wherein the proportion of the traffic capacity of each link which has been provisioned for data traffic is visually communicated by displaying a bar graph showing the traffic capacity of the link, and the proportion of that traffic capacity which has been provisioned for data traffic.

7. (Original) The method of claim 5 further comprising:

Appl. No. 10/025,628

when the optical components icon has been selected, visually communicating in the optical components panel a proportion of, the traffic capacity of each link of which the selected route is comprised, which has been provisioned for data traffic, which has been provisioned for data traffic at a selected speed.

8. (Original) The method of claim 1 wherein when the optical components icon has been selected, only graphical representations of those optical components having selected characteristics, are displayed.

9. (Original) The method of claim 1 further comprising:

when the channel viewer icon has been selected, upon selection of a longitudinal location along the selected route, displaying in association with each of the graphical representations of the channels, information respecting the longitudinal segment of the channel associated with the selected longitudinal location along the selected route, in tabular form.

10. (Original) The method of claim 9 wherein the graphical representations of the channels are parallel bars, and the selection of a longitudinal location along the selected route is effected by moving a slide tab displayed along the parallel bars.

11. (Original) A computer-readable medium having stored thereon, instructions for a computer system to display network management information for an optical network, said optical network comprising a plurality of nodes each comprising at least one optical component, and a plurality of links for transmitting optical signals between said plurality of nodes, said optical network further comprising at least one route of optical signal transmission, said route comprising a start node, an end node, and intermediate nodes and intermediate links through which an optical signal is transmitted between the start node and the end node on the route, wherein the intermediate links of said route are composed of a plurality of channels, and each of said channels is composed of at least one longitudinal segment, each of which longitudinal segments may be provisioned for data traffic by a network administrator, and wherein each of said optical signals is a multiplexed combination of a plurality of channel signals, each of said channel signals having associated therewith, a transmitter optical component and a receiver optical component, said instructions causing said computer system to:

Appl. No. 10/025,628

upon selection of a network topology icon:

identify in the plurality of nodes, add/drop nodes at which a channel signal may be added to, and/or dropped from, an optical signal on the optical network;

display a network topology panel; and

display in the network topology panel, a graphical representation of only those of the plurality of nodes which have been identified as add/drop nodes;

upon selection of an optical components icon:

await selection of a selected route;

upon selection of a selected route, identify the start node, at least one intermediate node, and the end node, of which the selected route is comprised;

display an optical components panel; and

display in the optical components panel graphical representations of at least one optical component of which the start node is comprised, at least one optical component of which the at least one intermediate node is comprised, and at least one optical component of which the end node is comprised, as identified for the selected route;

upon selection of a channel viewer icon:

await selection of a selected route;

upon selection of a selected route, identify each of the plurality of channels of which the links of the selected route are comprised;

display a channel viewer panel;

display in the channel viewer panel, a graphical representation of each of the plurality of channels identified for the selected route; and

Appl. No. 10/025,628

communicate in association with each of the graphical representations of the channels, which of the longitudinal segments of which the channel is comprised, has been provisioned for data traffic by the network administrator; and

upon selection of a transmitters/receivers icon:

await selection of a selected route;

upon selection of a selected route, identify information respecting the transmitter optical component and receiver optical component associated with the channel signal transmitted by each of the channels of which the links of the selected route are composed;

display a transmitters/receivers panel; and

display in tabular form in the transmitters/receivers panel, the information respecting each of the transmitter optical components and the receiver optical components identified for the selected route.

12. (Original) The computer-readable medium of claim 11 wherein said instructions further cause said computer system to:

when the network topology icon has been selected, display in the network topology panel, a graphical representation of those of the plurality of links which transmit optical signals between the add/drop nodes.

13. (Original) The computer-readable medium of claim 12 wherein said instructions further cause said computer system to:

when the network topology icon and a selected route have been selected, visually distinguish in the network topology, the graphical representations of the start node, the end node, those of the intermediate nodes at which a channel signal may be added to and/or dropped from an optical signal being transmitted on the selected route, and the intermediate links, of which the selected route is comprised.

Appl. No. 10/025,628

14. (Original) The computer-readable medium of claim 11 wherein when the optical components icon has been selected, the instructions cause said computer system to display the graphical representations of the optical components in a linear configuration, in a sequential order.

15. (Original) The computer-readable medium of claim 11 wherein said instructions further cause said computer system to:

when the optical components icon has been selected, visually communicate in the optical components panel, a proportion of a traffic capacity of each link of which the selected route is comprised, which has been provisioned for data traffic by a network administrator.

16. (Original) The computer-readable medium of claim 15 wherein the proportion of the traffic capacity of each link which has been provisioned for data traffic is visually communicated by displaying a bar graph showing the traffic capacity of the link, and the proportion of that traffic capacity which has been provisioned for data traffic.

17. (Original) The computer-readable medium of claim 15 wherein said instructions further cause said computer system to:

when the optical components icon has been selected, visually communicate in the optical components panel a proportion of, the traffic capacity of each link which has been provisioned for data traffic, which has been provisioned for data traffic at a selected speed.

18. (Original) The computer-readable medium of claim 11 wherein when the optical components icon has been selected, the instructions cause the computer system to display only graphical representations of those optical components having selected characteristics.

19. (Original) The computer-readable medium of claim 11 wherein said instructions further cause the computer system to:

when the channel viewer icon has been selected, upon selection of a longitudinal location along the selected route, display in association with each of the graphical representations of the channels, information respecting the longitudinal segment of the channel associated with the selected longitudinal location along the selected route, in tabular form.

Appl. No. 10/025,628

20. (Original) The computer-readable medium of claim 19 wherein the graphical representations of the channels are parallel bars, and the selection of a longitudinal location along the selected route is effected by moving a slide tab displayed along the parallel bars.

21. (Original) A network management computer system for displaying network management information for an optical network, said optical network comprising a plurality of nodes each comprising at least one optical component, and a plurality of links for transmitting optical signals between said plurality of nodes, said optical network further comprising at least one route of optical signal transmission, said route comprising a start node, an end node, and intermediate nodes and intermediate links through which an optical signal is transmitted between the start node and the end node on the route, wherein the intermediate links of said route are composed of a plurality of channels, and each of said channels is composed of at least one longitudinal segment, each of which longitudinal segments may be provisioned for data traffic by a network administrator, and wherein each of said optical signals is a multiplexed combination of a plurality of channel signals, each of said channel signals having associated therewith, a transmitter optical component and a receiver optical component, said computer system comprising:

a network database containing therein network information for the optical network;

a processor connected to said network database operable to retrieve network information from the network database;

a display connected to said processor for displaying network information;

network topology display means associated with said processor operable to cause the processor to:

retrieve from the network database, network information for the nodes;

Appl. No. 10/025,628

identify in the network information for the nodes, add/drop nodes at which a channel signal may be added to, and/or dropped from, an optical signal on the optical network;

display on the display, a network topology panel; and

display in the network topology panel, a graphical representation of only those of the plurality of nodes which have been identified as add/drop nodes;

optical components display means associated with said processor operable to cause the processor to:

await selection of a selected route;

upon selection of a selected route, retrieve network information for the selected route from the network database;

identify in the network information for the selected route, the start node, at least one intermediate node, and the end node, of which the selected route is comprised;

display on the display, an optical components panel; and

display in the optical components panel graphical representations of at least one optical component of which the start node is comprised, at least one optical component of which the at least one intermediate node is comprised, and at least one optical component of which the end node is comprised, as identified for the selected route;

channel viewer display means associated with said processor operable to cause the processor to:

await selection of a selected route;

Appl. No. 10/025,628

upon selection of a selected route, retrieve network information for the selected route from the network database;

identify in the network information for the selected route, each of the plurality of channels of which the links of the selected route are comprised;

display on the display a channel viewer panel;

display in the channel viewer panel, a graphical representation of each of the plurality of channels identified for the selected route; and

communicate in association with each of the graphical representations of the channels, which of the longitudinal segments of which the channel is comprised, has been provisioned for data traffic by the network administrator; and

transmitters/receivers display means associated with said processor operable to cause the processor to:

await selection of a selected route;

upon selection of a selected route, retrieve from the network database, network information for the selected route;

identify in the network information for the selected route, information respecting the transmitter optical component and receiver optical component associated with the channel signal transmitted by each of the channels of which the links of the selected route are composed;

display on the display, a transmitters/receivers panel; and

display in tabular form in the transmitters/receivers panel, the information respecting each of the transmitter optical components and the receiver optical components identified for the selected route.

Appl. No. 10/025,628

22. (Original) The computer system of claim 21 wherein said network topology display means is further operable to cause the processor to:

display in the network topology panel, a graphical representation of those of the plurality of links which transmit optical signals between the add/drop nodes.

23. (Original) The computer system of claim 22 wherein said network topology display means is further operable to cause the processor to:

when a selected route have been selected, visually distinguish in the network topology, the graphical representations of the start node, the end node, those of the intermediate nodes at which a channel signal may be added to and/or dropped from an optical signal being transmitted on the selected route, and the intermediate links, of which the selected route is comprised.

24. (Original) The computer system of claim 21 wherein said optical components display means is further operable to cause the processor to:

display the graphical representations of the optical components in a linear configuration, in a sequential order.

25. (Original) The computer system of claim 21 wherein said optical components display means is further operable to cause the processor to:

visually communicate in the optical components panel, a proportion of a traffic capacity of each link of which the selected route is comprised, which has been provisioned for data traffic by a network administrator.

26. (Original) The computer system of claim 25 wherein the proportion of the traffic capacity of each link which has been provisioned for data traffic is visually communicated by displaying a bar graph showing the traffic capacity of the link, and the proportion of that traffic capacity which has been provisioned for data traffic.

Appl. No. 10/025,628

27. (Original) The computer system of claim 25 wherein said optical components display means is further operable to cause the processor to:

visually communicate in the optical components panel a proportion of, the traffic capacity of each link which has been provisioned for data traffic, which has been provisioned for data traffic at a selected speed.

28. (Original) The computer system of claim 21 wherein said optical components display means is further operable to cause the processor to:

display only graphical representations of those optical components having selected characteristics.

29. (Original) The computer system of claim 21 wherein said channel viewer display means is further operable to cause the processor to:

upon selection of a longitudinal location along the selected route, display in association with each of the graphical representations of the channels, information respecting the longitudinal segment of the channel associated with the selected longitudinal location along the selected route, in tabular form.

30. (Original) The computer system of claim 29 wherein the graphical representations of the channels are parallel bars, and the selection of a longitudinal location along the selected route is effected by moving a slide tab displayed along the parallel bars.

31. (Cancelled)

32. (Original) A method in a computer system for displaying network management information for an optical network, said optical network comprising a plurality of optical components, and a plurality of optical connections for transmitting optical signals between said plurality of optical components, said optical network further comprising at least one route of optical signal transmission, said route comprising a start optical component, an end optical component, and intermediate optical components and intermediate optical connections through which an optical

Appl. No. 10/025,628

signal is transmitted between the start optical component and the end optical component on the route, the method comprising:

awaiting selection of a selected route;

upon selection of a selected route, identifying the start optical component, at least one intermediate optical component, and the end optical component, of which the selected route is comprised;

displaying an optical components panel; and

displaying in the optical components panel graphical representations of each of the start optical component, the at least one intermediate component, and the end optical component identified for the selected route.

33. (Original) A method in a computer system for displaying network management information for an optical network, said optical network comprising a plurality of nodes each comprising at least one optical component, and a plurality of links for transmitting optical signals between said plurality of nodes, said optical network further comprising at least one route of optical signal transmission, said route comprising a start node, an end node, and intermediate nodes and intermediate links through which an optical signal is transmitted between the start node and the end node on the route, wherein each of said links is composed of a plurality of channels, and each of said channels is composed of at least one longitudinal segment, each of which longitudinal segments may be provisioned for data traffic by a network administrator, the method comprising:

awaiting selection of a selected route;

upon selection of a selected route, identifying each of the plurality of channels of which the links of the selected route are comprised;

displaying a channel viewer panel;

displaying in the channel viewer panel, a graphical representation of each of the plurality of channels identified for the selected route; and

Appl. No. 10/025,628

communicating in association with each of the graphical representations of the channels, which of the longitudinal segments of which the channel is comprised, has been provisioned for data traffic by the network administrator.

34. (Original) A method in a computer system for displaying network management information for an optical network, said optical network comprising a plurality of nodes each comprising at least one optical component, and a plurality of links for transmitting optical signals between said plurality of nodes, said optical network further comprising at least one route of optical signal transmission, said route comprising a start node, an end node, and intermediate nodes and intermediate links through which an optical signal is transmitted between the start node and the end node on the route, wherein each of said links is composed of a plurality of channels, each of said channels being capable of transmitting a channel signal, each of said channel signals having associated therewith, a transmitter optical component and a receiver optical component, the method comprising:

awaiting selection of a selected route;

upon selection of a selected route, identifying information respecting the transmitter optical component and receiver optical component associated with the channel signal transmitted by each of the channels of which the links of the selected route are composed;

displaying a transmitters/receivers panel; and

displaying in tabular form in the transmitters/receivers panel, the information respecting each of the transmitter optical components and the receiver optical components identified for the selected route.

35. (Original) A method in a computer system for displaying network management information for an optical network, said optical network comprising a plurality of nodes each comprising at least one optical component, and a plurality of links for transmitting optical signals between said plurality of nodes, said optical network further comprising at least one route of optical signal transmission, said route comprising a start node, an end node, and intermediate nodes and

Appl. No. 10/025,628

intermediate links through which an optical signal is transmitted between the start node and the end node on the route, the method comprising:

upon selection of a selected node, displaying in tabular form in a routes panel, information respecting each route which includes the selected node.

36. (Original) A method in a computer system for displaying network management information for an optical network, said optical network comprising a plurality of nodes each comprising at least one optical component, and a plurality of links for transmitting optical signals between said plurality of nodes, said optical network further comprising at least one route of optical signal transmission, said route comprising a start node, an end node, and intermediate nodes and intermediate links through which an optical signal is transmitted between the start node and the end node on the route, said method comprising:

upon selection of a selected link, displaying in a tabular form in a routes panel, information respecting each route which includes the selected link.